



2tec2

high tech flooring

COLOURFUL


COLOURFUL



Roll • Tile




Zenith



Quasar




Corona




Fireball




Atmosphere



Zodiac




Orbital



Equinox



Aurora



Pulsar

STRIPES



Roll • Tile



Moonless Night Blue



Moonless Night Orange


BARCODE



Roll • Tile



Quartz



Diamond

CRACKED EARTH



Roll • Tile



Arid

HERRINGBONE

Roll



Oyster



Dune



Sandstone

LUSTRE



Roll • Tile



Morion Brown



Magnetite Grey

TECHNICAL DATA

Woven Jacquard top layer	900 g/m ² - 26.54 oz/yd ²	Foot traffic test ASTM D6119-12	Heavy traffic
Composition	83% vinyl - 7% fiberglass - 10% PET	 Walking test ISO 6356 AATCC 134-2006	< 2 kV Permanently antistatic
Backing	Vinyl + Felt	 Slip resistance EN 13893 ASTM C1028-07 DIN 51130 EN 13036-4	≥ ds 0,85 R9 65
 Total thickness ISO 1765	5,0 mm - 0.20"	 Impact sound reduction ISO 10140	19 dB
 Total weight ISO 8543	3000 g/m ² - 94.4 oz/yd ²	 Acoustical absorption ISO 354	α _w = 0,15
 Roll width EN ISO 24341	ca. 200 cm - ca. 6'7"	 Walking noise reduction EPLF 021029-3	SL70
 Roll length EN ISO 24341	ca. 30 m - 32.8 yd	 Castor chair suitability EN 985	Continuous use
 Tile size (16 pcs per box) EN 994	50 cm x 50 cm - 19.69" x 19.69"	 Light fastness ISO 105-B02	8
 Level of Use EN 1307 ASTM D5252	Class 33 Heavy commercial use	 Dimensional stability EN 986 - ISO 2551	Meets the requirements
 Reaction to fire EN 13501-1 ASTM E84	B _{f1} -s1 A rating	 Thermal resistance ISO 8302	Suitable for underfloor heating
Critical radiant flux ASTM E648 NFPA	0,84 W/cm ² Class I	Warranty	10 years* *Terms and conditions are available on request
Smoke density ASTM E622	< 300	 CE Certificate EN 14041	0493-CPR-0151

ENVIRONMENT & INDOOR AIR QUALITY

Recycled Content Yes	WELL V2 Compliant	Indoor Air Comfort Gold Pass		
Acoustical layer 70% recycled content	CDPH Standard Method V1.2 Pass	Blue Angel (DE UZ120) Pass		
REACH Compliant	French VOC Regulation A+ Certified	SundaHus B rating		
LEED V4.1 Pass	French CMR components Pass	EN 717-1 E1		
BREEAM International V6.0 Exemplary level	Belgian VOC Regulation Pass	M1 Protocol of July 2017 Pass		
BREEAM® NOR V6.0 Exemplary level	AGBB/ABG Pass	Plasticizer Content Phthalate Free		
				

INSTALLATION PATTERNS FOR TILES



Ashlar



Brick



Monolithic



Quarterturn